S1017

4

NONE

5-24-85

6

AND CHANGE WITHOUT NOTICE

TOLERANCE

DIMENSIONS ARE SUBJECT

NUMBER

APPROVED

СНЕСКЕD ВҮ **ТD**

DRAWN BY:
BS

VOID DATA


OR)

CAN ASSUME NO RESPONSIBILITY FOR USE OF

ROOF DRAINS

IRMA ROOF APPLICATIONS

FUNCTION: Used in roof systems where the insulated membrane assembly method of waterproofing is provided. Used where built-up felt and asphalt waterproofing is installed. A stainless steel extension gravel stop at height specified is supplied to retain the crushed gravel used in IRMA flat roof construction.



A (Pipe Size) = 02(50), 03(75), 04(100), 05(125) or 06(150)

Fig. 1017C CAULK OUTLET Fig. 1017Y NO-HUB OUTLET

recommended deck opening

with suffix -R	17(430) DIA
less suffix -R	14(355) DIA

*This Dimension to Internal Stop of Speedi-Set Gasket.

REGULARLY FURNISHED:

Duco Cast Iron Body with Flashing Clamp, Perforated Stainless Steel Extension, Gravel Stop and Polyethylene Dome.

NOTE: Dimensions shown in parentheses are in millimeters.

VARIATIONS:

Expansion Joint (Specify Fig. 1710)
Extension -E (Specify Height)
"L" Shaped Underdeck Clamp -CL

L Speedi-Set Service Weight
02(50), 03(75) & 04"(100) sizes only
LXH Speedi-Set Extra Heavy

02(50), 03(75) & 04"(100) sizes only

Sump Receiver -R Underdeck Clamp -C

Vandal Proof Dome -U T Threaded Outlet

OPTIONAL MATERIALS:

Aluminum Dome -AD Cast Iron Dome -CID

Galvanized Cast Iron Body & Collar -G Galvanized Cast Iron Dome -CIDG

Rough Bronze Dome -RBD

▲Optional domes' free area are as follows:

Aluminum 98 (632) Cast Iron 80 (516) Bronze 95 (613)

N M L K	7-30-19 9-17-15 06/03/09 5-26-99	Removed NOTE Added Flow Rate Note Added Optional Dome Notes Revised Opt. Material	MW TBW JJ CMD	CL BW CL BS	WEIGHT POUNDS	VOLUME CUBIC FEET	FIGURE NUMBER 1017
REV.	DATE	DESCRIPTION	BY	CKD. BY			