**S1416** 

4

NONE

APPROVED BY 9

VGD CHECKED BY

DRAWN BY:

IGURE NUMBER


OR VOID DATA

WE CAN ASSUME NO RESPONSIBILITY FOR USE

## HEAVY DUTY ROOF DRAIN FOR PARKING AREA

FUNCTION: Used in heavy traffic areas, such as parking decks, where waste water contains no sediment or debris and construction requires a shallow body. Large top area permits use where high flow is anticipated.

> Free Area 45 SQ IN (290) SQ CM



▲add 1/4" (6) when bronze top is specified.

Fig. 1416C . . . . CAULK OUTLET Fig. 1416T . . . . THREADED OUTLET Fig. 1416Y . . . . NO-HUB OUTLET

recommended deck opening

	acon opermig			
	17 (430) DIA			
less Suffix -R	14 (355) DIA			

A 017E	02	02 03 04 05 06 (50) (75) (100) (125) (150)			08	10	
ASIZE	(50)	(75)	(100)	(125)	(150)	(200)	(250)
В	5 (125) for Caulk, NO-HUB				6 (150)	6 (150)	

\*This Dimension to Internal Stop of Speedi-Set Gasket.

REGUL	ARLY F	URNISHED:
-------	--------	-----------

Duco Cast Iron Body, Flashing Collar and Heavy Duty Loose Set ADA Tractor Grate.

## **VARIATIONS:**

Dome Grate -D

"L" Shaped Underdeck Clamp -CL L Speedi-Set Service Weight

02(50), 03(75) & 04"(100) sizes only

LXH Speedi-Set Extra Heavy 02(50), 03(75) & 04"(100) sizes only

Square Top -S

Sump Receiver -R

Underdeck Clamp -C Vandal Proof -U

Sediment Bucket -B

## **OPTIONAL MATERIALS:**

Ductile Iron Grate -M Galvanized Cast Iron -G

Galvanized Cast Iron Dome -CIDG

Nickel Bronze Top -NB

Polished Bronze Top -PB

NOTE: Floor drains or area drains used to drain areas subject to rainfall should have an open area equal to twice the cross sectional area of the connecting pipe.

N M L K	2-4-16 8-6-15	Revised Regularly Furnished Revised Table Added Threaded Outlet, Rev Var. Added ADA to Tractor Grate	TBW TBW TBW JJ	TWK BW CL CL	_	VOLUME CUBIC FEET	FIGURE NUMBER
REV.	DATE	DESCRIPTION	BY	CKD. BY	1		•