




INTERNATIONAL FASTENERS, INC.

SPEC DATA SUBMITTAL SHEET



Daggerz™ Self Drill Eye Lag Screws Zinc Finish

Size	TPI	Ctn Qty	Daggerz™ Part Number	Hole Diameter	Thread Length	Flange Diameter
14 x 2	14	2,000	ELSDZ1420	3/16"	3/4"	9/16"
14 x 3	14	1,000	ELSDZ1430	3/16"	2"	9/16"

<i>material:</i>	C1022 LOW CARBON STEEL, CORE HARDNESS: HV240-425
<i>finish:</i>	Zinc Finish provides 24 hour minimum salt spray corrosion resistance
<i>application:</i>	used to attach wire for interior suspended ceiling systems; drywall or insulation to steel

Meets or exceeds the following specifications:

ASTM A510	Specification for General Requirements for Wire Rods and Coarse Round Wire, Carbon Steel (Minimum grade 1018)
ASTM B117	Practice for Operating Salt Spray (Fog) Apparatus
SAE J78	Standard for Dimensional, Mechanical and Performance Requirements

Ultimate Value Chart

	DIAMETER	Nom Screw Dia	22 Gauge	20 Gauge	18 Gauge	16 Gauge	14 Gauge	12 Gauge
Tension (Pull) Lbs 1 pc	14-14	0.250	233	282	442	813	957	1344
Shear (Metal to Metal)	14-14	0.250	235	338	445	841	1001	1218

These figures are offered only as a guide and are not guaranteed in any way by International Fasteners, Inc.
 Appropriate safety factors should be applied to these values for specific purposes.
 All International Fasteners, Inc. Fasteners are manufactured to IFI's Performance Specifications and Print Drawings.

ELSDZ