



Maze Nails

Product Specification Sheet

Hot-Dip Galvanized Plain Shank Asphalt & Fiberglass Shingle Nails

Stock Number: R103

| | |
|-----------------------------|---------------------------|
| MATERIAL | Medium Carbon Steel |
| LENGTH | 1-15/32" OAL |
| SHANK DIAMETER | 0.121" |
| HEAD DIAMETER | .375" |
| SHANK STYLE | Smooth |
| POINT STYLE | 40 degree diamond |
| COATING | Double Hot-Dip Galvanized |
| APPROX. NAILS PER LB | 173.0 |

Product Description

Designed for the secure application of asphalt and fiberglass shingles on new construction and re-roofing jobs. STORMGUARD® Double Hot-Dipped Zinc-Coating provides extra corrosion-resistance in sea coastal areas. Manufactured to meet federal spec. ASTM F1667 and ASTM spec. A-153 for hot-dip zinc coating. Nails should be long enough to penetrate 3/4" into the wood deck lumber, or completely through plywood decking. All Maze Nails are 100% Made in the U.S.A. SIZES AND QUANTITIES COMMONLY USED On A New Roof – 1-1/4" - 320 nails per sq. or 1-3/4 lbs. Over An Old Roof – 1-3/4" - 320 nails per sq. or 2-1/4 lbs.



Disclaimer: This image represents an entire series of nails, so the length may not be the exact match to the nail in this spec sheet

100% MADE IN THE USA

Generated on: 6/17/2020