

Maze Nails

Product Specification Sheet

Hot-Dip Galvanized Ring Shank Split-Less® Wood Siding Nail

Stock Number: S229A

MATERIAL

LENGTH

SHANK DIAMETER

HEAD DIAMETER

SHANK STYLE

POINT STYLE

COATING

APPROX. NAILS PER LB

Medium Carbon Steel

2-31/32" OAL

0.092"

.219"

Ring Thread

50 degree diamond

Double Hot-Dip Galvanized

157.0

Product Description

Specially designed for split-prone woods such as cedar and redwood. Slim, sturdy shank and special blunt point virtually eliminate splits. STORMGUARD® doubledipped in molten zinc. Ring shank for additional holding power. Checkered head enhances paint adhesion on colormatched nails. High count greatly reduces per nail cost. Especially popular for sidings scheduled for finishing with paints or pigmented stains. For jobs that will be left natural or treated with a clear or semitransparent finish, we recommend our Type 304 Stainless Steel "SLIM-IIM"® Nails. Note: Use Type 316 Stainless Steel Fasteners for the highest degree of corrosion-resistance in environments such as sea-coastal areas.



Disclaimer: This image represents an entire series of nails, so the length may not be the exact match to the nail in this spec sheet

100% MADE IN THE USA

Generated on: 6/10/2020