

ELECTRIC DRINKING FOUNTAIN

A132.8-VR Series

MODEL A132408S-VR

BARRIER FREE, VANDAL RESISTANT, BI-LEVEL, WALL MOUNTED CHILLED DRINKING FOUNTAIN WITH 32" TRIM PANEL

STANDARD FEATURES

- Child Or Adult Ada Compliant (When Properly Installed)
- 18 Gauge, 304 Stainless Steel Basin And Flush Mounted Chrome Plated Brass Button
- Polished Stainless Steel, Vandal Resistant, Anti-rotation, Non-squirt Bubbler
- 100-mesh Inlet Strainer
- Vandal Resistant Screws
- Integral P-Trap
- Mounting Frame
- 32 Inch Trim Panel And Louvered Grille

SUGGESTED SPECIFICATIONS

Model A132408S-VR is a Vandal Resistant, Wall Mounted, Bi-Level pressure Chilled Drinking Fountain that shall deliver a minimum of 8.0 GPH (30.3 LPH) of water at 50°F (10°C) cooled from 80°F (26.7°C) inlet water and 90°F (32.2°C) ambient. Unit shall be made from 18 gauge, 304 stainless steel with a brushed finish. Unit shall be activated by Chrome Plated Brass Pushbutton using less than 5 pounds of force. Cooling system shall use R-134a refrigerant and be capillary tube regulated. Cooling system shall use R-134a refrigerant and be capillary tube regulated. An adjustable thermostat with an off position shall regulate the refrigeration system. Bubblers shall be polished stainless steel with nonsquirt features and operate on a water pressure range of 20-105 psig. Unit shall have uniquely designed, two-piece contoured bowls with P-Traps integral to the unit. Unit shall be listed by Underwriters Laboratories for both the US and Canada and is compliant to the Air Conditioning and Refrigeration Institute Standard 1010. Unit is certified to ANSI A117.1, Public Law 111-380 (NO-LEAD), CHSC 116875 and NSF/ANSI 61, Section 9. Fixture meets ADA, ADA Standing Person, and ADA Child requirements when mounted appropriately.

Model Number	GPH*	Rated Watts	Full Load Amps	Approx. Shipping Weight
A132408S-VR	8.0	390	4.6	130 lbs.

*GPH of 50°F water at 90°F ambient room temperature and 80°F inlet water temperature. Compressor motor operates on 115 Volt / 60 Hz single phase.













A132.8-VR



"INDOOR USE ONLY"

MODEL:

(Must Specify)

FLEXIBLE BUBBLER (LOW FLOW)

A132208F-VR Bronze Finish

☐ A132308F-VR Gold Finish (High Polish)
☐ A132408F-VR Satin stainless Finish

LEAD-FREE STAINLESS STEEL BUBBLER

☐ A132208S-VR Bronze Finish

☐ A132308S-VR Gold Finish (High Polish)

☐ A132408S-VR Satin stainless Finish (Shown)

OPTIONS

(additional costs may be incurred)

☐ -HP High polished stainless steel

☐ -RBL Reverse bi-level

□ -SK4-18 Skirt kit, stainless steel, for upper unit□ -WF1 1500 gallon capacity, NSF 42+53,

1 micron lead reduction filter

☐ -WF3 3000 gallon capacity, NSF 42+53,

1 micron lead reduction filter

□ -220V 220 volt / 50 Hz compressor (**(€**)



U.S. Green Building Council





MARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com



Revised: 09/13/2021





ELECTRIC DRINKING FOUNTAIN


A132.8-VR Series

MODEL A132408S-VR

BARRIER FREE, VANDAL RESISTANT, BI-LEVEL, WALL MOUNTED CHILLED DRINKING FOUNTAIN WITH 32" TRIM PANEL







GENERAL NOTES:

- 1. ALL DIMENSIONS ARE IN INCHES [MM].
- *2. DIMENSIONS SHOWN ARE FOR RECOMMENDED ADULT HEIGHT. ADJUST VERTICAL DIMENSIONS AS NECESSARY TO COMPLY WITH FEDERAL, STATE, & LOCAL CODES.
- 3. WATER LINES FROM CHILLER TO FOUNDATION SHOULD BE COVERED WITH SPONGE FOAM RUBBER OR ICE WATER TYPE INSULATION OF ADEQUATE THICKNESS.

Murdock Mfg.™ warrants that its products are free from defects in material or workmanship under normal use and service for a period of one year from date of shipment. Murdock's liability under this warranty shall be discharged solely by replacement or repair of defective material, provided Murdock™ is notified in writing within one year from date of shipment, F.O.B. Industry, California.

SUMMARY /AL FOR :TURING	Model Number & Options Company	Quantity	All dimensions are subject to manufactures tolerance of plus or minus ½" nominal and subject to change without notice. Murdock assumes no responsibility for use void or superseded data. Dimensi may change with the addition of optional accessories. Murdock Mf, Member of Morris Group International™. Please visit www.murdockmfg.com for most current specifications.
SELECTION SUMMAR & APPROVAL FOR MANUFACTURING	Contact Signature (Approval for Manufacturing)	Title	

MURDOCK MFG. • 15125 Proctor Avenue • City of Industry, CA 91746 USA Phone 800-453-7465 or 626-333-2543 • Fax 626-855-4860 • www.murdockmfg.com

Member of MORRIS GROUP